

# VDS<sup>®</sup> by FORSTER<sup>®</sup> DOORS

45, 60 and 90 Minute Door Assemblies

## CLASSIFICATION

## PRODUCT DESCRIPTION



VDS 60 and 90 minute fire rated doors provide maximum vision area while maintaining narrow stiles and rails. These systems complement our fully-insulated VDS framing systems where doors are requested.

## TECHNICAL SPECIFICATIONS

Testing/Standard Conformity	NFPA 80, NFPA 251 NFPA 252, UL 10B, UL 10C, CAN/ULC-S101
Finish Options	Powder Coat, Enamel, Kynar
Custom Colors <sup>1</sup>	Yes
Fabrication	Welded
Certification	Underwriters Laboratories - UL LLC
Fabricated in the US	Yes
Glazing Options	Contraflam 60, 90, 120
Single/Double Doors	Yes
Weight (lbs/lin. ft; kg/lin. ft)	5-7 (2.3-3.2) *Weight per unit provided prior to shipment*
Max Door Leaf Size	60 min 48" x 120", 90 min 42" x 96"

## MAXIMUM DIMENSIONS

\*D.L.O. size limitations dependent on maximum exposed glass area\*

Maximum Height (in.; m)	120 (3.048) Call for details
Maximum Width (in.; m)	57 (1.448) Call for details

## DETAILS



<sup>1</sup>Surcharge may apply

Rev. 11.11.15 The information published in this document is correct at the time of going to press. Such information may be subject to change and products may be modified.